




FLEXIBLE CONTROL CABLES

also available with black and blue conductors and black or orange jacket



CC 600 P red Oil resistant, tear resistant, flexible PUR control cable with red conductors



Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2

02640510 5 x 1,0 mm² CC 600 P red 18 AWG/5c 02641805 AWM Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2 CE

A
29

CC 600 P red is a multi-conductor, 600 V, 80°C oil resistant control cable. The specially blended polyurethane jacket provides an excellent chemical and abrasion resistance as well as being tear resistant and halogen free with low flame propagation. For use in harsh environments.

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
Insulation:	PVC, T12 acc. to DIN VDE 0281 part 1 + HD 21.1
Color code:	red conductors with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 conductors
Stranding:	in layers, 2 conductors and > 8 conductors wrapping with non-woven tape over the outer layer
Inner jacket:	above 12 AWG: PVC TM2 acc. to DIN VDE 0281 part 1 + HD 21.1
Jacket material:	PU acc. to UL 758
Jacket color:	gray

Outstanding features:

- oil resistant
- abrasion resistant
- notch resistant
- good chemical resistance

Technical data:

Nominal voltage:	DIN VDE U ₀ /U 300/500 V	UL/CSA 600 V
Testing voltage U:	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2	
Min. bending radius		
<i>fixed installation:</i>	< 12 mm = 3 x O.D. > 12 mm = 4 x O.D.	
<i>free movement:</i>	< 12 mm = 5 x O.D. > 12 mm = 6 x O.D.	
Radiation resistance:	5 x 10 ⁷ cJ/kg	
Temperature range	DIN VDE static: flexing:	UL/CSA: up to +80 °C +5/+70 °C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2 UL VW-1, CSA FT1 and FT2	
Oil resistance:	very good - oil rating 60°C acc. to UL 1581	
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.	
Absence of harmful substances:	acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24, see page N/25	

item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 20 AWG (17/32) • 0.50 mm²					▶ 18 AWG (30/32) • 1.00 mm²					▶ 14 AWG (46/30) • 2.50 mm²				
02642002	2	0.244	6.2	32	02641802	2	0.272	6.9	43	02641402	2	0.343	8.7	75
02642003	3	0.252	6.4	38	02641803	3	0.280	7.1	51	02641403	3	0.358	9.1	94
02642004	4	0.268	6.8	44	02641804	4	0.303	7.7	61	02641404	4	0.386	9.8	114
02642005	5	0.291	7.4	53	02641805	5	0.327	8.3	74	02641405	5	0.421	10.7	140
02642007	7	0.311	7.9	65	02641807	7	0.378	9.6	99	02641407	7	0.496	12.6	194
02642009	9	0.374	9.5	81	02641809	9	0.429	10.9	116	02641409	9	0.587	14.9	235
02642012	12	0.398	10.1	97	02641812	12	0.453	11.5	139	02641412	12	0.602	15.3	277
02642018	18	0.457	11.6	136	02641818	18	0.528	13.4	200	02641418	18	0.717	18.2	412
02642025	25	0.539	13.7	178	02641825	25	0.630	16.0	267	02641425	25	0.913	23.2	595
02642030	30	0.555	14.1	206	02641830	30	0.657	16.7	312	▶ 12 AWG (52/28) • 4.00 mm²				
02642034	34	0.598	15.2	233	02641834	34	0.709	18.0	355	02641203	3	0.469	11.9	157
02642042	42	0.654	16.6	290	02641842	42	0.756	19.2	431	02641204	4	0.512	13.0	194
02642050	50	0.709	18.0	331	02641850	50	0.886	22.5	542	02641205	5	0.547	13.9	230
					▶ 16 AWG (27-29/30) • 1.50 mm²					▶ 10 AWG (78/28) • 6.00 mm²				
					02641602	2	0.295	7.5	53	02641004	4	0.579	14.7	264
					02641603	3	0.307	7.8	65	02641005	5	0.634	16.1	324
					02641604	4	0.331	8.4	78	▶ 8 AWG (77/26) • 10.00 mm²				
					02641605	5	0.358	9.1	94	02640804	4	0.728	18.5	433
					02641607	7	0.417	10.6	128	Other dimensions and colors are possible on request.				
					02641609	9	0.480	12.2	151					
					02641612	12	0.504	12.8	182					
					02641618	18	0.587	14.9	263					
					02641625	25	0.709	18.0	360					
					02641630	30	0.732	18.6	420					
					02641634	34	0.791	20.1	528					
					02641642	42	0.902	22.9	629					
					02641650	50	0.984	25.0	726					

E-mail: info@sabcable.com



Web site: www.sabcable.com