

SILICONE CABLES

SC 123 Silicone insulated strands with fiber-glass braid



SC 123 is a high temperature single conductor silicone wire recommended for use in applications where temperature exceeds the maximum rating of traditional plastic and rubber insulated wires. This cable is a flexible, cost-effective alternative to teflon wire. Recommended applications include foundries, steel mills and glass factories, and other high temperature processes and is recommended wherever an overall abrasion resistant covering is required.

Construction:

Conductor:	tinned copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
Insulation:	Besilen® EI2 acc. to DIN VDE 0282 part 1 and HD 22.1
Standard color:	nature
Braiding:	fiberglass
Impregnation:	impregnating lacquer

Outstanding features:

- halogen-free
- flexible at low temperatures
- heat resistant
- flexible

Technical data:

Nominal voltage:	U ₀ /U 300/300 V
Testing voltage:	2000 V
Min. bending radius:	7.5 x O.D.
Radiation resistance:	2 x 10 ⁷ cJ/kg
Temperature range	
<i>static:</i>	-40/+180 °C
<i>flexing:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
Zero halogen:	acc. to DIN VDE 0472 part 815 and IEC 60754-1
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
Corrosivity:	in compliance with IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 - no development of corrosive conflagration gases
Absence of harmful substances:	acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24, see page M/25

item no.	mm ²	AWG	nominal inch	outer-ø mm	cable weight ≈ lbs/mft	
▶ 01230050	0.50	20	(15/32)	0.094	2.4	7
▶ 01230070	0.75	19	(23/32)	0.106	2.7	11
▶ 01230100	1.00	18	(30/32)	0.110	2.8	12
▶ 01230150	1.50	16	(27/30)	0.126	3.2	15
▶ 01230250	2.50	14	(46/30)	0.154	3.9	24
▶ 01230400	4.00	12	(52/29)	0.177	4.5	34
▶ 01230600	6.00	10	(78/28)	0.205	5.2	50
▶ 01231000	10.00	8	(77/26)	0.287	7.3	91
▶ 01231600	16.00	6	(129/26)	0.327	8.3	133
▶ 01232500	25.00	4	(200/26)	0.402	10.2	206
▶ 01233500	35.00	2	(280/26)	0.449	11.4	271
▶ 01235000	50.00	1	(400/26)	0.555	14.1	384
▶ 01237000	70.00	2/0	(554/26)	0.594	15.1	509
▶ 01239500	95.00	3/0	(484/24)	0.728	18.5	702

Other dimensions and colors are possible on request.