


STANDARD SERIES NPT THREAD CABLE GLANDS

Water tight, easy to assemble, good strain relief, wide clamping range, multipurpose applications, easy handling.

TECHNICAL DETAILS:

Material	Polyamide 6
Color	RAL 7001 (Gray) RAL 9005 (Black)
Protection Class	IP 68.5 bar
Temp. Range	-30°C to + 80°C permanent
Oper. Temperature	Up to + 150°C intermittent
Seal	Neoprene



NPT Thread Strain Relief Cord Connectors

NPT Size	Part Number Gray	Part Number Black	Thread Length	Wrenching Flats	Diameter Range
NPT 3/8	BSPA-01	BSPA-21	.590	.866	.197 - .394
NPT 1/2	BSPB-02	BSPB-22	.590	.945	.236 - .472
NPT 3/4	BSPD-03	BSPD-23	.590	1.299	.511 - .709
NPT 1	BSP-04	BSP-24	.709	1.654	.709 - .984
NPT 1 1/4	BSPE-05	BSPE-25	.709	2.087	.709 - .984

Glands with Reducer Bushings

NPT Size	Part Number Gray	Part Number Black	Thread Length	Wrenching Flats	Diameter Range
NPT 3/8	BSPA-01R	BSPA-21R	.590	0.866	.118 - .276
NPT 1/2	BSPB-02R	BSPB-22R	.590	0.945	.197 - .354
NPT 3/4	BSPD-03R	BSPD-23R	.590	1.299	.354 - .630
NPT 1	BSP-04R	BSP-24R	.709	1.654	.472 - .787
NPT 1 1/4	BSPE-05R	BSPE-25R	.709	2.087	.472 - .787

Various colors, materials and sizes available upon request.

E-mail: info@sabcable.com



Web site: www.sabcable.com