


STANDARD SERIES PG & NPT THREAD CABLE GLANDS

The latest technology suitable for the highest demands, water tight, offering excellent strain relief.

TECHNICAL DETAILS:

Material	Brass, Nickel Plated
Sealing Ring	Neoprene
Protection Class	IP 68
Temp. Range	-40°C to + 100°C
Clamping Insert	Polyamide 6
O Ring	NBR



PG Thread Strain Relief Brass Nickel Plated

PG Metric Size	Part Number	Thread Diameter (mm)	Thread Length (mm)	Wrenching Flats (mm)	Diameter Range (mm)	Diameter Range (inches)
PG 7	BSBC-01	13	6.0	14	3.0 - 6.5	.118 - .256
PG 9	BSBC-02	16	6.0	17	4.0 - 8.0	.157 - .315
PG 11	BSBC-03	19	6.0	20	5.0 - 10.0	.197 - .394
PG 13.5	BSBC-04	21	6.5	22	6.0 - 12.0	.236 - .472
PG 16	BSBC-05	23	6.5	24	10.0 - 14.0	.394 - .551
PG 21	BSBC-06	29	7.2	30	13.0 - 18.0	.512 - .709
PG 29	BSBC-07	37	8.0	40	18.0 - 25.0	.709 - .985
PG 36	BSBC-08	47	9.0	50	22.0 - 32.0	.867 - 1.260
PG 42	BSBC-09	54	12.0	58	30.0 - 38.0	1.182 - 1.497
PG48	BSBC-10	59	14.0	64	34.0 - 44.0	1.340 - 1.733

PG Thread Strain Relief Brass Nickel Plated with Long Thread

PG Metric Size	Part Number	Thread Diameter (mm)	Thread Length (mm)	Wrenching Flats (mm)	Diameter Range (mm)	Diameter Range (inches)
PG 7	BSBE-01	13	10.0	14	3.0 - 6.5	.118 - .256
PG 9	BSBE-02	16	10.0	17	4.0 - 8.0	.157 - .315
PG 11	BSBE-03	19	10.0	20	5.0 - 10.0	.197 - .394
PG 13.5	BSBE-04	21	10.0	22	6.0 - 12.0	.236 - .473
PG 16	BSBE-05	23	10.0	24	10.0 - 14.0	.394 - .552
PG 21	BSBE-06	29	12.0	30	13.0 - 18.0	.512 - .709
PG 29	BSBE-07	37	12.0	40	18.0 - 25.0	.709 - .985
PG 36	BSBE-08	47	14.0	50	22.0 - 32.0	.867 - 1.260
PG 42	BSBE-09	54	16.0	58	30.0 - 38.0	1.182 - 1.497
PG 48	BSBE-10	59	18.0	64	34.0 - 44.0	1.339 - 1.733

NPT Thread Strain Relief Brass Nickel Plated

NPT Size	Part Number	Thread Diameter (mm)	Thread Length (mm)	Wrenching Flats (mm)	Diameter Range (mm)	Diameter Range (inches)
3/8	BNBC-01	16.0	15.0	17	4.0 - 8.0	.157 - .315
1/2	BNBC-02	21.0	13.0	22	6.0 - 12.0	.236 - .473
3/4	BNBC-03	29.0	13.0	30	13.0 - 18.0	.512 - .709

Various colors, materials and sizes available upon request.

E-mail: info@sabcable.com



Web site: www.sabcable.com