


STANDARD SERIES PG THREAD CABLE GLANDS

Liquid tight, easy to assemble, good strain relief, wide clamping range, multipurpose applications, easy handling.



TECHNICAL DETAILS:

Material	Polyamide 6
Color	RAL 7001 (Gray) RAL 9005 (Black)
Protection Class	IP 68.5 bar
Temp. Range	-30°C to + 80°C permanent
Oper. Temperature	Up to + 150°C intermittent
Seal	Neoprene

PG Thread Strain Relief Cord Connectors

Pg Metric Size	Part Number Gray	Part Number Black	Mounting Hole (Inches)	Mounting Hole (mm)	Thread Length (Inches)	Thread Length (mm)	Wrenching Flats (Inches)	Wrenching Flats (mm)	Diameter Range (Inches)	Diameter Range (mm)
Pg 7	BS-01	BS-21	.512	13	.315	8	.591	15	.118 - .256	3.0 - 6.5
Pg 9	BS-02	BS-22	.630	16	.315	8	.749	19	.158 - .315	4.0 - 8.0
Pg 11	BS-03	BS-23	.749	19	.315	8	.867	22	.197 - .394	5.0 - 10.0
Pg 13, 5	BS-04	BS-24	.827	21	.355	9	1.064	27	.236 - .473	6.0 - 12.0
Pg 16	BS-05	BS-25	.906	23	.394	10	1.064	27	.394 - .552	10.0 - 14.0
Pg 21	BS-06	BS-26	1.143	29	.433	11	1.300	33	.512 - .709	13.0 - 18.0
Pg 29	BS-07	BS-27	1.458	37	.433	11	1.655	42	.709 - .985	18.0 - 25.0
Pg 36	BS-08	BS-28	1.852	47	.512	13	2.088	53	.867 - 1.261	22.0 - 32.0
Pg 42	BS-09	BS-29	2.128	54	.512	13	2.364	60	1.182 - 1.497	30.0 - 38.0
Pg 48	BS-10	BS-30	2.325	59	.552	14	2.561	65	1.340 - 1.734	34.0 - 44.0

Glands with Reducer Bushings

Pg Metric Size	Part Number Gray	Part Number Black	Mounting Hole (inches)	Mounting Hole (mm)	Thread Length (inches)	Thread Length (mm)	Wrenching Flats (inches)	Wrenching Flats (mm)	Diameter Range (inches)	Diameter Range (mm)
Pg 7	BSR-01	BSR-21	.512	13	.315	8	.591	15	.079 - .197	2.0 - 5.0
Pg 9	BSR-02	BSR-22	.630	16	.315	8	.749	19	.079 - .236	2.0 - 6.0
Pg 11	BSR-03	BSR-23	.749	19	.315	8	.867	22	.118 - .276	3.0 - 7.0
Pg 13, 5	BSR-04	BSR-24	.827	21	.355	9	1.064	27	.197 - .355	5.0 - 9.0
Pg 16	BSR-05	BSR-25	.906	23	.394	10	1.064	27	.276 - .473	7.0 - 12.0
Pg 21	BSR-06	BSR-26	1.143	29	.433	11	1.300	33	.355 - .630	9.0 - 16.0
Pg 29	BSR-07	BSR-27	1.458	37	.433	11	1.655	42	.473 - .788	12.0 - 20.0
Pg 36	BSR-08	BSR-28	1.852	47	.512	13	2.088	53	.788 - 1.024	20.0 - 26.0
Pg 42	BSR-09	BSR-29	2.128	54	.512	13	2.364	60	.985 - 1.221	25.0 - 31.0
Pg 48	BSR-10	BSR-30	2.325	59	.552	14	2.561	65	1.143 - 1.379	29.0 - 35.0

Various colors, materials and sizes available upon request.

E-mail: info@sabcable.com



Web site: www.sabcable.com