

Continuous Flex Cables for Track

SD 960 CY

Shielded continuous flex data cable for small bending radius



Marking for SD 960 CY 7852425:

SAB BRÖCKSKES · D-VIERSEN · 7852502 25 x 0.25 mm² SD 960 CY 24 AWG/25c 7852425 AWM Style 21083 80°C 300V CE

Construction:

Conductor:	bare copper strands, extra fine wires
Insulation:	PVC, Tl2 acc. to EN 50363-3 + VDE 0207-363-3
Color code:	US 2, see below
Stranding:	specially adjusted layering with non-woven tape over each layer
Wrapping:	non-woven tape
Shielding:	tinned copper braiding
Wrapping:	non-woven tape
Jacket material:	PVC, TM2 acc. to EN 50363-3 + VDE 0207-363-3
Jacket color:	black (RAL 9005)

Outstanding features:

- very good EMC characteristics
- very good flexibility
- small bending radius
- UV resistant jacket

Technical data:

Peak operating voltage:	max. 350 V
Voltage UL:	300 V
Testing voltage:	conductor/conductor: 1500 V conductor/shielding: 1200 V
Min. bending radius: continuously flexing:	7.5 x O.D.
Radiation resistance:	8 x 10 ⁷ cJ/kg
Temperature range: static: flexing:	DIN VDE UL/CSA: up to +80°C -30/+70°C +5/+70°C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, UL VW-1
Oil resistance:	acc. to our internal standard, see page O/29
Approvals:	UR AWM, CE, EAC, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors	nominal outer-ø inch mm	cable weight ≈lbs/mft
► 26 AWG (≈ 18/38) ▪ 0.14 mm²			
7852602	2	0.177 4.5	17
7852603	3	0.185 4.7	20
7852604	4	0.205 5.2	24
7852605	5	0.220 5.6	28
7852607	7	0.252 6.4	38
7852610	10	0.295 7.5	45
7852614	14	0.335 8.5	60
7852618	18	0.366 9.3	73
7852625	25	0.433 11.0	100

item no.	no. of conductors	nominal outer-ø inch mm	cable weight ≈lbs/mft
► 24 AWG (≈ 32/38) ▪ 0.25 mm²			
7852402	2	0.193 4.9	20
7852403	3	0.205 5.2	24
7852404	4	0.217 5.5	28
7852405	5	0.244 6.2	36
7852407	7	0.280 7.1	43
7852410	10	0.335 8.5	60
7852414	14	0.362 9.2	75
7852418	18	0.398 10.1	92
7852425	25	0.492 12.5	134

item no.	no. of conductors	nominal outer-ø inch mm	cable weight ≈lbs/mft
► 22 AWG (≈ 42/38) ▪ 0.34 mm²			
7852202	2	0.201 5.1	22
7852203	3	0.213 5.4	26
7852204	4	0.228 5.8	31
7852205	5	0.252 6.4	40
7852207	7	0.291 7.4	49
7852210	10	0.346 8.8	69
7852214	14	0.378 9.6	86
7852218	18	0.425 10.8	114
7852225	25	0.512 13.0	153

Other dimensions and colors are available on request

US 2 color code:

#1- black, #2- white, #3- red, #4- green, #5- orange, #6- blue, #7- white-black, #8- red-black, #9- green-black, #10- orange-black, #11- blue-black, #12- black-white, #13- red-white, #14- green-white, #15- blue-white, #16- black-red, #17- white-red, #18- orange-red, #19- blue-red, #20- red-green, #21- orange-green, #22- black-white-red, #23- white-black-red, #24- red-black-white, #25- green-black-white



Possible on request:

- 20 AWG & 19 AWG
- with gray jacket and colored conductors with reference to DIN 47100