


Continuous Flex Cables for Track

S 980 CP

High speed continuous flex heavy duty shielded halogen-free polyurethane control cable



Marking for S 980 CP 77842012:

SAB BRÖCKSKES · D-VIERSEN · 77841205 x 0.5 mm² S 980 CP 20 AWG/7c 77842012 AWM Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2 CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 6
Insulation:	TPE
Color code:	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
Stranding:	specially adjusted layering with non-woven tape over each layer
Inner jacket:	special SABIX®
Wrapping:	non-woven tape
Shielding:	tinned copper braiding
Wrapping:	non-woven tape
Jacket material:	PUR, TPU acc. to EN 50363-3 + VDE 0207-363-3-10-2 with matte surface
Jacket color:	gray (RAL 7000)

Outstanding features:

- free from paint wetting impairment
substances (PWIS-free)
- flexible at low temperatures
- travel > 10 m is possible
- good EMC characteristics
- high abrasion resistance
- small bending radius
- halogen-free

Technical data:

Nominal voltage:	Uo/U 300/500 V
Voltage UL/CSA:	600 V
Testing voltage:	conductor/conductor: 2000 V conductor/shielding: 2000 V
Min. bending radius: <i>continuously flexing:</i>	7.5 x O.D.
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range: <i>static:</i> <i>flexing:</i>	DIN VDE UL/CSA: up to +80°C -50/+90°C -40/+90°C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, CSA FT1, FT2
Oil resistance:	very good - TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Chemical resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Continuous flexibility:	very good
Approvals:	UR AWM, CSA AWM, CE, EAC, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors incl. ground	nominal outer-ø inch mm	cable weight ≈lbs/mft
▶ 20 AWG (≈ 28/34) • 0.50 mm ²			
77842003	3	0.339 8.6	58
77842004	4	0.354 9.0	66
77842005	5	0.382 9.7	75
77842007	7	0.425 10.8	92
77842012	12	0.496 12.6	137
77842018	18	0.579 14.7	192
77842025	25	0.673 17.1	255
▶ 19 AWG (≈ 42/34) • 0.75 mm ²			
77841903	3	0.354 9.0	65
77841904	4	0.374 9.5	74
77841905	5	0.406 10.3	85
77841907	7	0.461 11.7	116
77841912	12	0.543 13.8	171
77841918	18	0.630 16.0	238
77841925	25	0.736 18.7	306
▶ 18 AWG (≈ 56/34) • 1.00 mm ²			
77841803	3	0.362 9.2	71
77841804	4	0.386 9.8	82
77841805	5	0.413 10.5	95
77841807	7	0.476 12.1	129
77841812	12	0.559 14.2	201
77841818	18	0.634 16.1	269
77841825	25	0.760 19.3	350

item no.	no. of conductors incl. ground	nominal outer-ø inch mm	cable weight ≈lbs/mft
▶ 16 AWG (≈ 84/34) • 1.50 mm ²			
77841603	3	0.374 9.5	80
77841604	4	0.425 10.8	102
77841605	5	0.453 11.5	127
77841607	7	0.520 13.2	168
77841612	12	0.618 15.7	258
77841618	18	0.709 18.0	346
77841625	25	0.909 23.1	521
▶ 14 AWG (≈ 140/34) • 2.50 mm ²			
77841403	3	0.449 11.4	123
77841404	4	0.476 12.1	146
77841405	5	0.528 13.4	175
77841407	7	0.610 15.5	248
77841412	12	0.736 18.7	376
77841418	18	0.921 23.4	566
77841425	25	1.071 27.2	725
▶ 12 AWG (≈ 224/34) • 4.00 mm ²			
77841203	3	0.496 12.6	167
77841204	4	0.543 13.8	205
77841205	5	0.598 15.2	251
▶ 10 AWG (≈ 186/32) • 6.00 mm ²			
77841003	3	0.579 14.7	234
77841004	4	0.622 15.8	294
77841005	5	0.681 17.3	334

item no.	no. of conductors incl. ground	nominal outer-ø inch mm	cable weight ≈lbs/mft
▶ 8 AWG (≈ 320/32) • 10.00 mm ²			
77840803	3	0.740 18.8	372
77840804	4	0.807 20.5	458
77840805	5	0.957 24.3	607
▶ 6 AWG (≈ 504/32) • 16.00 mm ²			
77840603	3	0.878 22.3	528
77840604	4	0.992 25.2	703
77840605	5	1.110 28.2	845
▶ 4 AWG (≈ 760/32) • 25.00 mm ²			
77840404	4	1.169 29.7	1011
77840405	5	1.283 32.6	1211
▶ 2 AWG (≈ 1083/32) • 35.00 mm ²			
77840204	4	1.307 33.2	1289
77840205	5	1.437 36.5	1545

Other dimensions and colors are available on request