


# Industrial Ethernet Cables CAT 5

**DR PN 689 P Highflex** PUR Reeling Profinet cable/ CAT 5 cable

**S PN 668** PUR Hybrid cable continuous flex suitable for cable tracks with UL recognition

**RT PN 668** PUR Profinet cable suitable for robots



S · D-VIERSEN · DR PN 689 P Highflex 2x2x22AWG CE



Marking for DR PN 689 P Highflex 06892202:

SAB BRÖCKSKES · D-VIERSEN · DR PN 689 P Highflex 2x2x22AWG CE



<b>Construction:</b>	DR PN 689 P Highflex reeling Profinet cable	DR PN 689 P Highflex reeling CAT 5 cable	S PN 668 Hybrid Hybrid cable type C continuous flex	RT PN 668 Profinet cable suitable for robots
<b>Item numbers:</b>	06892202	06899001	06689010	06689001
<b>Dimensions:</b>	2 x 2 x 22 AWG	4 x 2 x 26 AWG	2 x 2 x 22 AWG + 4 x 16 AWG	2 x 2 x 22 AWG
<b>Conductor:</b>	tinned copper strands, fine wires	tinned copper strands, fine wires	22 AWG: tinned copper strands, extra fine wires 16 AWG: bare copper strands acc. to IEC 60228, VDE 0295, class 6	tinned copper strands, extra fine wires
<b>Insulation:</b>	SABIX®	SABIX®	22 AWG: SABIX® 16 AWG: TPE	PE
<b>Color code:</b>	blue, yellow, white, orange	blue, orange, green, brown + 4 white conductors with consecutive numbers	22 AWG: blue, yellow, white, orange 16 AWG: black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334	blue, yellow, white, orange
<b>Stranding:</b>	in layers	twisted to pairs and pairs together	22 AWG: in layers/ together in layers	in layers
<b>Wrapping:</b>	PETP foil	PETP foil	22 AWG: PETP foil	woven tape, alu foil
<b>Inner jacket:</b>	SABIX®	SABIX®	22 AWG: SABIX®	—
<b>Wrapping:</b>	alu foil	alu foil	22 AWG: alu foil	—
<b>Shielding:</b>	tinned copper braiding	tinned copper braiding	—	tinned copper braiding
<b>Wrapping:</b>	non-woven tape	non-woven tape	non-woven tape	non-woven tape
<b>Jacket material:</b>	PUR/supporting braid/PUR	PUR/supporting braid/PUR	PUR	PUR
<b>Jacket color:</b>	green (similar RAL 6018)	black (similar RAL 9005)	green (similar RAL 6018)	green (similar RAL 6018)

<b>Technical data:</b>	DR PN 689 P Highflex reeling Profinet cable	DR PN 689 P Highflex reeling CAT 5 cable	S PN 668 Hybrid Hybrid cable type C continuous flex	RT PN 668 Profinet cable suitable for robots
<b>Peak operating voltage:</b>	max. 350 V	max. 350 V	max. 350 V	max. 350 V
<b>Voltage UL:</b>	—	—	300 V	—
<b>Testing voltage:</b> conductor/conductor: conductor/shielding:	1500 V 1200 V	1500 V 1200 V	2000 V 2000 V	1500 V 1200 V
<b>Min. bending radius:</b>	for laying and installation (fixed installation): for repeated winding action (flexible): guided on deflection pulleys (flexible):	5 x O.D. 10 x O.D. 12 x O.D.	fixed installation: 5 x O.D. flexible: 10 x O.D. continuous flex: 12 x O.D.	fixed installation: 5 x O.D. flexible: 10 x O.D. torsion angle: ± 180°/m
<b>Temperature range VDE:</b> static: flexible:	-40/+90°C -30/+90°C	-40/+90°C -30/+90°C	UL: up to +80°C -40/+90°C -30/+90°C	-40/+70°C -30/+70°C
<b>Halogen-free:</b>	acc. to IEC 60754-1 + VDE 0482-754-1	acc. to IEC 60754-1 + VDE 0482-754-1	acc. to IEC 60754-1 + VDE 0482-754-1	acc. to IEC 60754-1 + VDE 0482-754-1
<b>Oil resistance:</b>	TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2		TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2	
<b>Characteristic impedance:</b>	100Ω ± 10Ω, accomplishes the electrical and transmission requirements with high frequency acc. to EN 50288-2-2 + VDE 0819-2-2 (CAT 5 acc. to EN 50173-1)			
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union, see page O/30			

item no.	type	jacket color	dimensions AWG	nominal outer-ø inch	mm	cable weight ≈lbs/mft	ohmic resistance at 20°C acc. to VDE 0812 max. Ω/km
▶ 06892202	DR PN 689 P Highflex	green (similar RAL 6018)	22 (≈ 19/34)/2pr	0.323	8.2	56	58.8
▶ 06899001	DR PN 689 P Highflex	black (similar RAL 9005)	26 (≈ 19/38)/4pr	0.343	8.7	57	139
▶ 06689010	S PN 668 Hybrid	green (similar RAL 6018)	22 (≈ 19/34)/2pr + 16 (≈ 84/34)/4c	0.394	10.0	106	58.0 / 13.3
▶ 06689001	RT PN 668	green (similar RAL 6018)	22 (≈ 19/34)/2pr	0.276	7.0	42	58.0

Other dimensions and colors are available on request



www.sabcable.com  
866-722-2974 ■ info@sabcable.com

