



Dome Plugs

Sealing plug for cable glands based on clamping range

Dome Plugs are used for sealing cable glands when no cable is being used.



Technical data:

Material:	Polyamide 6
Temperature range:	
<i>permanent:</i>	-20°C to +100°C
<i>intermittent:</i>	-30°C to +150°C
Flammability:	V2 (according to UL 94)

Part Number		Dome Plug Fit into Clamping Range Ø min - max		Plug (ØP)		Length (PL)		Outer (ØD)		Height (h)	
Gray	Black	Standard Seal inches	Reducing Seal inches	inches	mm	inches	mm	inches	mm	inches	mm
DPG-01	DPB-01	-	0.079 - 0.197	0.157	4.0	0.472	12.0	0.362	9.2	0.157	4.0
DPG-02	DPB-02	0.118 - 0.256	-	0.252	6.4	0.472	12.0	0.362	9.2	0.157	4.0
DPG-03	DPB-03	-	0.079 - 0.236	0.197	5.0	0.551	14.0	0.413	10.5	0.197	5.0
DPG-04	DPB-04	0.157 - 0.315	-	0.315	8.0	0.539	13.7	0.413	10.5	0.185	4.7
DPG-05	DPB-05	-	0.118 - 0.276	0.276	7.0	0.591	15.0	0.524	13.3	0.224	5.7
DPG-06	DPB-06	0.197 - 0.394	-	0.382	9.7	0.354	9.0	0.524	13.3	0.209	5.3
DPG-07	DPB-07	-	0.197 - 0.354	0.335	8.5	0.512	13.0	0.622	15.8	0.303	7.7
DPG-08	DPB-08	0.236 - 0.472	-	0.472	12.0	0.512	13.0	0.622	15.8	0.315	8.0
DPG-09	DPB-09	0.276 - 0.512	-	0.512	13.0	0.551	14.0	0.622	15.8	0.295	7.5
DPG-10	DPB-10	-	0.276 - 0.472	0.433	11.0	0.531	13.5	0.709	18.0	0.335	8.5
DPG-11	DPB-11	0.394 - 0.551	-	0.535	13.6	0.531	13.5	0.709	18.0	0.343	8.7
DPG-12	DPB-12	-	0.354 - 0.512	0.512	13.0	0.571	14.5	0.787	20.0	0.276	7.0
DPG-13	DPB-13	0.433 - 0.669	-	0.646	16.4	0.571	14.5	0.783	19.9	0.287	7.3
DPG-14	DPB-14	-	0.354 - 0.63	0.551	14.0	0.551	14.0	0.866	22.0	0.374	9.5
DPG-15	DPB-15	0.512 - 0.709	-	0.701	17.8	0.551	14.0	0.866	22.0	0.394	10.0
DPG-16	DPB-16	-	0.433 - 0.591	0.634	16.1	0.610	15.5	0.945	24.0	0.354	9.0
DPG-17	DPB-17	0.591 - 0.827	-	0.803	20.4	0.610	15.5	0.949	24.1	0.362	9.2
DPG-18	DPB-18	-	0.472 - 0.787	0.776	19.7	0.591	15.0	1.122	28.5	0.382	9.7
DPG-19	DPB-19	0.709 - 0.984	-	0.984	25.0	0.591	15.0	1.122	28.5	0.382	9.7
DPG-20	DPB-20	-	0.63 - 0.906	0.807	20.5	0.622	15.8	1.240	31.5	0.362	9.2
DPG-21	DPB-21	0.748 - 1.102	-	1.075	27.3	0.622	15.8	1.240	31.5	0.362	9.2
DPG-22	DPB-22	-	0.787 - 1.024	1.012	25.7	0.669	17.0	1.449	36.8	0.421	10.7
DPG-23	DPB-23	0.866 - 1.26	-	1.252	31.8	0.669	17.0	1.449	36.8	0.421	10.7
DPG-24	DPB-24	-	0.984 - 1.22	1.205	30.6	0.795	20.2	1.705	43.3	0.469	11.9
DPG-25	DPB-25	1.181 - 1.496	-	1.496	38.0	0.795	20.2	1.705	43.3	0.469	11.9
DPG-26	DPB-26	-	1.142 - 1.378	1.362	34.6	0.886	22.5	2.008	51.0	0.630	16.0
DPG-27	DPB-27	1.339 - 1.732	-	1.740	44.2	0.886	22.5	2.008	51.0	0.630	16.0