

Compensation & Extension Cables

Besilen® insulated cables

A 1 LB twisted · A 16 LB



A 1 LB twisted



A 16 LB



Also available
with cross-sections
1.0 mm², 0.75 mm²,
0.5 mm² and 0.22 mm²

Construction:

Insulation:	Besilen® EI2 acc. to EN 50363-1 + VDE 0207-363-1
Stranding:	A 1 LB: 2 conductors together A 16 LB: 2 conductors parallel
Shape:	A 1 LB: round A 16 LB: oval
Conductor construction:	strand

Technical data:

Min. bending radius:	7.5 x O.D.
Radiation resistance:	2 x 10 ⁷ cJ/kg
Temperature range of insulation:	<i>static:</i> -40/+180°C <i>flexible:</i> -25/+180°C <i>short time use:</i> +250°C
Insulation resistance:	> 1MΩ x km
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
Corrosivity:	in compliance with IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

Type: Conductor cross section: Outer diameter: Weight/100m:	A 1 LB twisted: 1.5 mm ² approx. 5.0 mm approx. 3.3 kg	A 16 D 1.5 mm ² approx. 2.5 x 5.0 mm approx. 3.2 kg
---	---	--

IEC 60584

for thermocouple	EMK at 100°C in mV	cable type	A 1 LB twisted item no.	A 16 D item no.
Type T	4.28	TX	04048958	04068958
Type J	5.27	JX	04048952	04068952
Type K	4.10	KCA	04048995	04068995
Type K	4.10	KCB	04048999	04068999
Type K	4.10	KX	04048954	04068954
Type E	6.32	EX	04048953	04068953
Type R/S	0.65	R/SCB	04048997	04068997
Type N	2.77	NC	04048991	04068911

DIN 43710 / 43714 (not valid for type B*)

We continue to manufacture compensating and extension cables with color code acc. to DIN 43714 and the basic values of DIN 43710.

for thermocouple	EMK at 100°C in mV	cable type	A 1 LB twisted item no.	A 16 D item no.
Type L	5.37	LX	04048992	04068992
Type K	4.10	KCA	04048994	04068994
Type R/S	0.65	R/SCB	04048996	04068996
Type U	4.25	UX	04048998	04068998
Type B*	0.00	BC-100	04048901	04068901
Type B*	0.033	BC-200	04048902	04068902

* Not standardized compensating cable for thermocouples type B with application temperatures up to 100°C resp. 200°C.
C = compensating cables · X = extension cables