


# Continuous Flex Cables for Track

## S 980 CP

High speed continuous flex heavy duty shielded halogen-free polyurethane control cable



Marking for S 980 CP 77842012:

SAB BRÖCKSKES · D-VIERSEN · 77841205 x 0.5 mm<sup>2</sup> S 980 CP 20 AWG/7c 77842012 AWM Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2 CE

### Construction:

<b>Conductor:</b>	bare copper strands acc. to IEC 60228, VDE 0295, class 6
<b>Insulation:</b>	TPE
<b>Color code:</b>	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Inner jacket:</b>	special SABIX®
<b>Wrapping:</b>	non-woven tape
<b>Shielding:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	PUR, TMPU acc. to EN 50363-3 + VDE 0207-363-3-10-2 with matte surface
<b>Jacket color:</b>	gray (RAL 7000)

### Outstanding features:

- free from paint wetting impairment substances (PWIS-free)
- flexible at low temperatures
- travel > 10 m is possible
- good EMC characteristics
- high abrasion resistance
- small bending radius
- halogen-free

### Technical data:

<b>Nominal voltage:</b>	Uo/U 300/500 V	
<b>Voltage UL/CSA:</b>	600 V	
<b>Testing voltage:</b>	conductor/conductor: 2000 V conductor/shielding: 2000 V	
<b>Min. bending radius:</b> <i>continuously flexing:</i>	7.5 x O.D.	
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg	
<b>Temperature range:</b> <i>static:</i> <i>flexing:</i>	DIN VDE -50/+90°C	UL/CSA: up to +80°C
<b>Halogen-free:</b>	acc. to IEC 60754-1 + VDE 0482-754-1	
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, CSA FT1, FT2	
<b>Oil resistance:</b>	very good - TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2	
<b>Chemical resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.	
<b>Continuous flexibility:</b>	very good	
<b>Approvals:</b>	UR AWM, CSA AWM, CE, RoHS	
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page O/30	

B  
27

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
<b>▶ 20 AWG (≈ 28/34) ▪ 0.50 mm<sup>2</sup></b>				
77842003	3	0.339	8.6	58
77842004	4	0.354	9.0	66
77842005	5	0.382	9.7	75
77842007	7	0.425	10.8	92
77842012	12	0.496	12.6	137
77842018	18	0.579	14.7	192
77842025	25	0.673	17.1	255
<b>▶ 19 AWG (≈ 42/34) ▪ 0.75 mm<sup>2</sup></b>				
77841903	3	0.354	9.0	65
77841904	4	0.374	9.5	74
77841905	5	0.406	10.3	85
77841907	7	0.461	11.7	116
77841912	12	0.543	13.8	171
77841918	18	0.630	16.0	238
77841925	25	0.736	18.7	306
<b>▶ 18 AWG (≈ 56/34) ▪ 1.00 mm<sup>2</sup></b>				
77841803	3	0.362	9.2	71
77841804	4	0.386	9.8	82
77841805	5	0.413	10.5	95
77841807	7	0.476	12.1	129
77841812	12	0.559	14.2	201
77841818	18	0.634	16.1	269
77841825	25	0.760	19.3	350

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
<b>▶ 16 AWG (≈ 84/34) ▪ 1.50 mm<sup>2</sup></b>				
77841603	3	0.374	9.5	80
77841604	4	0.425	10.8	102
77841605	5	0.453	11.5	127
77841607	7	0.520	13.2	168
77841612	12	0.618	15.7	258
77841618	18	0.709	18.0	346
77841625	25	0.909	23.1	521
<b>▶ 14 AWG (≈ 140/34) ▪ 2.50 mm<sup>2</sup></b>				
77841403	3	0.449	11.4	123
77841404	4	0.476	12.1	146
77841405	5	0.528	13.4	175
77841407	7	0.610	15.5	248
77841412	12	0.736	18.7	376
77841418	18	0.921	23.4	566
77841425	25	1.071	27.2	725
<b>▶ 12 AWG (≈ 224/34) ▪ 4.00 mm<sup>2</sup></b>				
77841203	3	0.496	12.6	167
77841204	4	0.543	13.8	205
77841205	5	0.598	15.2	251
<b>▶ 10 AWG (≈ 186/32) ▪ 6.00 mm<sup>2</sup></b>				
77841003	3	0.579	14.7	234
77841004	4	0.622	15.8	294
77841005	5	0.681	17.3	334

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
<b>▶ 8 AWG (≈ 320/32) ▪ 10.00 mm<sup>2</sup></b>				
77840803	3	0.740	18.8	372
77840804	4	0.807	20.5	458
77840805	5	0.957	24.3	607
<b>▶ 6 AWG (≈ 504/32) ▪ 16.00 mm<sup>2</sup></b>				
77840603	3	0.878	22.3	528
77840604	4	0.992	25.2	703
77840605	5	1.110	28.2	845
<b>▶ 4 AWG (≈ 760/32) ▪ 25.00 mm<sup>2</sup></b>				
77840404	4	1.169	29.7	1011
77840405	5	1.283	32.6	1211
<b>▶ 2 AWG (≈ 1083/32) ▪ 35.00 mm<sup>2</sup></b>				
77840204	4	1.307	33.2	1289
77840205	5	1.437	36.5	1545

Other dimensions and colors are available on request

