


Halogen-free Cables

SABIX® CC 625 FRNC M Control cable with numbered conductors



Marking for SABIX® CC 625 FRNC M 62521612:

SAB BRÖCKSKES · D-VIERSEN · 62521612 12 x 1.5 mm² SABIX® CC 625 FRNC M 16 AWG/12c 62521215 AWM Style 21089 75°C 600V CSA AWM I/II A/B 80°C 600V FT1 CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 5
Insulation:	SABIX®
Color code:	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
Stranding:	in layers
Jacket material:	SABIX®
Jacket color:	gray (RAL 7000)

Outstanding features:

- low smoke halogen-free (LSHF)
- UL recognized, CSA approved
- no flame propagation
- flame retardant and self-extinguishing
- flexible

Technical data:

Nominal voltage:	Uo/U 300/500 V
Voltage UL/CSA:	600 V
Testing voltage:	conductor/conductor: 3000 V
Min. bending radius:	4 x O.D. fixed installation: free movement: 6 x O.D.
Temperature range:	UL: up to +75°C CSA: up to +80°C <i>static</i> DIN VDE: -40/+90°C <i>flexible:</i> -30/+90°C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Burning characteristics:	no flame propagation acc. to IEC 60332-3-24 + VDE 0482-332-3-24 resp. IEC 60332-3-25 + VDE 0482-332-3-25 cat. C resp. D Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
Corrosivity:	in compliance with IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases
Smoke density:	acc. to IEC 61034 + VDE 0482-1034
Flexibility:	good
Approvals:	UR AWM, CSA AWM, CE, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
► 20 AWG (≈ 16/32) ▪ 0.50 mm²				
62522002	2	0.205	5.2	27
62522003	3	0.217	5.5	32
62522004	4	0.232	5.9	38
62522005	5	0.252	6.4	44
62522007	7	0.276	7.0	56
62522008	8	0.323	8.2	70
62522009	9	0.350	8.9	79
62522010	10	0.358	9.1	81
62522012	12	0.366	9.3	91
62522014	14	0.386	9.8	103
62522016	16	0.413	10.5	119
62522018	18	0.437	11.1	132
62522025	25	0.531	13.5	181
62522030	30	0.547	13.9	208
62522034	34	0.598	15.2	239
62522040	40	0.650	16.5	283
62522041	41	0.650	16.5	288
62522061	61	0.760	19.3	409

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
► 19 AWG (≈ 23/32) ▪ 0.75 mm²				
62521902	2	0.224	5.7	32
62521903	3	0.236	6.0	38
62521904	4	0.256	6.5	46
62521905	5	0.280	7.1	54
62521907	7	0.311	7.9	71
62521908	8	0.366	9.3	89
62521909	9	0.390	9.9	97
62521910	10	0.398	10.1	100
62521912	12	0.417	10.6	118
62521914	14	0.437	11.1	132
62521916	16	0.469	11.9	152
62521918	18	0.492	12.5	168
62521925	25	0.598	15.2	231
62521930	30	0.618	15.7	267
62521934	34	0.673	17.1	304
62521940	40	0.732	18.6	359
62521941	41	0.732	18.6	366
62521961	61	0.866	22.0	528

item no.	no. of conductors incl. ground	outer-ø ±10% inch	outer-ø ±10% mm	cable weight ≈lbs/mft
► 18 AWG (≈ 30/32) ▪ 1.00 mm²				
62521802	2	0.232	5.9	36
62521803	3	0.248	6.3	44
62521804	4	0.268	6.8	54
62521805	5	0.295	7.5	65
62521807	7	0.323	8.2	83
62521808	8	0.378	9.6	102
62521809	9	0.413	10.5	116
62521810	10	0.421	10.7	120
62521812	12	0.433	11.0	137
62521814	14	0.453	11.5	155
62521818	18	0.512	13.0	198
62521825	25	0.622	15.8	271
62521830	30	0.654	16.6	320
62521834	34	0.709	18.0	365
62521840	40	0.768	19.5	429
62521841	41	0.768	19.5	454
62521861	61	0.902	22.9	626

Continued on next page

K
25

Halogen-free Cables

SABIX® CC 625 FRNC M

Control cable with numbered conductors



Marking for SABIX® CC 625 FRNC M 62521612:

SAB BRÖCKSKES · D-VIERSEN · 62521612 12 x 1.5 mm² SABIX® CC 625 FRNC M 16 AWG/12c 62521215 AWM Style 21089 75°C 600V CSA AWM I/II A/B 80°C 600V FT1 CE

item no.	no. of conductors incl. ground	outer-ø		cable weight ≈lbs/mft
		±10% inch	±10% mm	
▶ 16 AWG (≈ 27-29/30) ▪ 1.50 mm²				
62521602	2	0.256	6.5	46
62521603	3	0.272	6.9	57
62521604	4	0.299	7.6	71
62521605	5	0.327	8.3	87
62521607	7	0.366	9.3	112
62521608	8	0.429	10.9	136
62521609	9	0.465	11.8	153
62521610	10	0.476	12.1	161
62521612	12	0.488	12.4	184
62521614	14	0.512	13.0	209
62521618	18	0.587	14.9	271
62521625	25	0.713	18.1	375
62521630	30	0.736	18.7	435
62521634	34	0.807	20.5	502
62521640	40	0.874	22.2	587
62521641	41	0.874	22.2	593
62521661	61	1.024	26.0	861

item no.	no. of conductors incl. ground	outer-ø		cable weight ≈lbs/mft
		±10% inch	±10% mm	
▶ 14 AWG (≈ 46/30) ▪ 2.50 mm²				
62521402	2	0.307	7.8	70
62521403	3	0.327	8.3	86
62521404	4	0.362	9.2	108
62521405	5	0.398	10.1	131
62521407	7	0.441	11.2	173
62521408	8	0.528	13.4	212
62521409	9	0.563	14.3	234
62521410	10	0.583	14.8	252
62521412	12	0.602	15.3	290
62521418	18	0.717	18.2	425
62521425	25	0.878	22.3	585
▶ 12 AWG (≈ 52/28) ▪ 4.00 mm²				
62521203	3	0.382	9.7	126
62521204	4	0.425	10.8	160
62521205	5	0.476	12.1	198
62521207	7	0.528	13.4	261

item no.	no. of conductors incl. ground	outer-ø		cable weight ≈lbs/mft
		±10% inch	±10% mm	
▶ 10 AWG (≈ 78/28) ▪ 6.00 mm²				
62521003	3	0.449	11.4	182
62521004	4	0.500	12.7	230
62521005	5	0.559	14.2	286
▶ 8 AWG (≈ 77/26) ▪ 10.00 mm²				
62520804	4	0.677	17.2	409
62520805	5	0.760	19.3	508
▶ 6 AWG (≈ 122/26) ▪ 16.00 mm²				
62520604	4	0.831	21.1	611
▶ 4 AWG (≈ 190/26) ▪ 25.00 mm²				
62520404	4	1.043	26.5	991
▶ 2 AWG (≈ 272/26) ▪ 35.00 mm²				
62520204	4	1.189	30.2	1346

Other dimensions and colors are available on request