



Construction:

Conductor:	bare copper strands acc. to IEC 60228
Insulation:	4 x 2 x AWG 26: FEP 4 x 1.0 mm ² : TPE
Color code:	4 x 2 x AWG 26: white-blue/blue, white-orange/orange, white-green/green, white-brown/brown 4 x 1.0 mm ² : black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334
Jacket material:	PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Jacket color:	black (RAL 9005)

item no.	dimensions AWG/c	nominal outer-ø	
		inch	mm
▶ 6949001	26/4pr + 18/4c	0.496	12.6

Other dimensions and colors are possible on request.

Technical Data:

Peak operating voltage	Nominal voltage	Testing voltage	Temperature range	Min. bending radius	Absence of harmful substances
4 x 2 x AWG 26: max. 350 V	4 x 1.0 mm ² : 300/500 V	26 AWG/4pr: conductor/conductor 1500 V conductor/shielding 1200 V 18 AWG/4c: conductor/conductor 2000 V	flexible application: -40/+90°C	recommended: 10 x O.D.	acc. to RoHS directive of the European Union



**Teach Pendant cables
on request!**

