

Tray Cables

TR 600 Auto HD

Continuous flex heavy duty tray cable
Type TC-ER



600V FT4 CSA AWM I/II A/B 90C 600V FT4 RoHS CE



Marking for TR 600 Auto HD 32321604:

SAB NORTH AMERICA TR 600 Auto HD 16AWG/4c P/N 32321604 (UL) TC-ER 90C DRY 75 C WET 600V OIL RES I/II SUN RES DIR BUR OR
WTTTC 1000V OR AWM 21270 105C 600V OR c(UL) CIC-TC PVC/N 600V FT4 CSA AWM I/II A/B 90C 600V FT4 RoHS CE

Construction:

Conductor:	bare copper strands class M
Insulation:	special formulated PVC/Nylon
Color code:	black with numerical print* and one green/yellow earth ground** *Alpha-Numeric Alternate and Inverted, ie: 1-ONE
Stranding:	in layers with fleece tape separator
Jacket material:	TPE
Jacket color:	black (RAL 9005)

Technical data:

Voltage:	UL-AWM / (UL) / c(UL): 600 V (UL) WTTTC: 1000 V
Testing voltage:	2500 V
Min. bending radius:	<i>fixed installation:</i> 4 x O.D. <i>free movement:</i> 6 x O.D. <i>continuous flexing:</i> 10 x O.D.
Temperature range:	UL-AWM up to +105°C (UL) / c(UL) / CSA-AWM: up to +90°C <i>static:</i> -40°C
Cold bend test:	-40°C
Burning characteristics:	(UL) / CSA FT4
Oil resistance I & II:	yes
Exposed runs:	yes
Approvals:	UL TC-ER, UL WTTTC, UR AWM, c(UL) CIC-TC, CSA AWM, CE, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30
Alt. Color code:	** Add B at the end of Part No. for Blue conductors: blue conductors with numbers; one white-blue conductor and green/yellow ground ** Add R at the end of Part No. for Red conductors: red conductors with numbers; one white-red conductor and green/yellow ground

E
20

Outstanding features:

- heavy duty tray cable and control and instrumentation cable
- UL-AWM 21270 recognized for 105°C
- extremely oil resistant
- WTTTC: UL subject 2277
- TC: UL standard 1277
- CSA listed
- NFPA 79 for Industrial Machinery
- c(UL) CIC-TC FT4
- continuous flex applications
- Class 1 Div 2 per NEC Article 501.4 (B)

item no.	no. of conductors incl. ground	outer-ø inch	outer-ø mm	cable weight ≈lbs/mft
▶ 18 AWG				
32321803	3	0.302	7.7	48
32321804	4	0.325	8.3	58
32321805	5	0.350	8.9	75
32321807	7	0.405	10.3	94
32321812	12	0.480	12.2	134
32321818	18	0.589	15.0	214
32321825	25	0.714	18.1	307
▶ 16 AWG				
32321603	3	0.336	8.5	63
32321604	4	0.364	9.2	77
32321605	5	0.394	10.0	98
32321607	7	0.458	11.6	125
32321612	12	0.580	14.7	204
32321618	18	0.669	17.0	300
32321625	25	0.819	20.8	423

item no.	no. of conductors incl. ground	outer-ø inch	outer-ø mm	cable weight ≈lbs/mft
▶ 14 AWG				
32321403	3	0.361	9.2	82
32321404	4	0.391	9.9	102
32321405	5	0.423	10.7	125
32321407	7	0.495	12.6	169
32321412	12	0.625	15.9	282
▶ 12 AWG				
32321203	3	0.420	10.7	115
32321204	4	0.458	11.6	145
32321205	5	0.499	12.7	189
32321207	7	0.621	15.8	264
32321212	12	0.742	18.8	398
▶ 10 AWG				
32321003	3	0.506	12.9	179
32321004	4	0.590	15.0	248
32321005	5	0.642	16.3	298

item no.	no. of conductors incl. ground	outer-ø inch	outer-ø mm	cable weight ≈lbs/mft
▶ 8 AWG				
32320804	4	0.756	19.2	385
32320805	5	0.826	21.0	465
▶ 6 AWG				
32320603	3	0.767	19.5	426
32320604	4	0.879	22.3	580
▶ 4 AWG				
32320404	4	1.061	26.9	845
32320405	5	1.177	29.9	1035
▶ 2 AWG				
32320204	4	1.235	31.4	1278
32320205	5	1.363	34.6	1575

2 conductor cable does not have ground
Other dimensions and colors are available on request



Possible on request:

- with gray jacket as well as blue or red conductors

* For blue conductors add B at end of P/N, for red add an R, ie 32321404B

